

Panel mounted socket
Part no. 1506




- screw terminals
- 20° inclination
- 32 A sockets optional fitted with auxiliary contact

Technical specifications

Ampere	32 A
Poles	4 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 67
Flange	100x92 mm
Fixing hole	85x77 mm
Inclination	20 °
Weight	291 g
Declaration of Conformity	DE,VDE, CN,CQC

Drawing



Drawing 1 MB 251 Dim. in mm	Amp. Poles	16			32		
		3	4	5	3	4	5
a	73.5	100	100	100	100	100	100
b	64	92	92	92	92	92	92
c	52	60	62	64	64	66	66
d	60	85	85	85	85	85	85
e	52	77	77	77	77	77	77
f	5.5	5.5	5.5	5.5	5.5	5.5	5.5
g	8	8	8	8	8	8	8
g.1	2	2	2	2	2	2	2
h	84	100	105	109	109	113	113
i	78	85	96	103	103	110	110
k	43	32	32	53	53	45	45
l	52	55	65	67	67	72	72
lt	60	63	72	82	82	85	85
o	20°	20°	20°	20°	20°	20°	20°
Terminal for cond. cross section (mm²) min.-max.	1.5	1.5	1.5	2.5	2.5	2.5	2.5
	-4	-4	-4	-10	-10	-10	-10