



LISTED

53Z2

Model # 2P20GR

### Cat # 20FR Female Panel Mount

- PANEL CUTOUT 760 X 2 020, 16 GAUGE, 060 MATERIAL
- PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 INJUST TORQUE

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO <u>CONDUCTIVE</u>

PANEL. MOUNTING STRAP PROVIDES CONDUCTIVE
PATH BETWEEN GROUNDING TERMINAL AND PANEL.

- WIRE TERMINATION TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS
  - SLIP WIRE SHOE (PROVIDED) OVER STRANDS INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 INJUR TOROUE
- #8 RING TERMINAL MAY SE CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 IN/LBS

SEE REVERSESIDE FOR DEVICE DIMENSIONS

### CONNECTOR



Model # 2P20GR

#### Cat # 20FR | Female Panel Mount

- PANEL CUTOUT .760 X 2 020, 16 GAUGE, 060 MATERIAL
- PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 IN/LBS TORQUE

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO CONDUCTIVE PANEL MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL

- WIRE TERMINATION TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES! PANEL MOUNTS
  - SLIP WIRE SHOE (PROVIDED) OVER STRANDS, INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/LB TORQUE
  - #8 RING TERMINAL MAY 86 CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 IN/LBS

SEE REVERSE SIDE FOR DÉVICE DIMENSIONS

### CONNECTOR

LISTED 53Z2

Mode! #2P20GR

#### Cat # 20FR Female Panel Mount

- PANEL CUTOUT 768 X 2 920, 16 GAUGE, 060 MATERIAL
- POSH DEVICE REARWARD (HROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 IN/LBS TORQUE

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO <u>CONDUCTIVE</u> <u>PANEL</u>, MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL.

- WIRE TERMINATION TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS:
- SLIP WIRE SHOE (PROVIDED) OVER STRANDS INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/LB TOROUE
- #8 RING TERMINAL MAY BE CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 INLES

SEE REVERSE SIDE FOR DEVICE DIMENSIONS



LISTED

53Z2

ONNECTOR

Model # 2P20GR

#### Cat # 20FR Female Panel Mount

- PANEL CUTOUT 760 X 2 020, 16 GAUGE, 060 MATERIAL
- PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 INJUST TORQUE

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO CONDUCTIVE PANEL MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL.

- WIRE TERMINATION IT WO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS
- SLIP WIRE SHOE (PROVIDED) OVER STRANDS INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/L8 TORQUE
- #8 RING TERMINAL MAY BE CRIMPED ONTO WIRE & AJSACHED WITH TERMINAL SCREW AT 12 INC.85

SFÈ REVERSE SIDE FOR DEVICE DIMENSIONS

## CONNECTOR



LISTED 53Z2

Model # 2P20GR

### Cat # 20FR Female Panel Mount

- PANEL CUTOUT 760 X 2 020, 16 GAUGE, 960 MATERIAL
- PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 IN/LBS TORQUE

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO CONDUCTIVE PANEL. MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL.

- WIRE TERMINATION TWO METHODS OF WIRE ERMINATION ARE OFFERED FOR THE BAILS PANEL MOUNTS
- SEP WIRE SHOE (PROVIDED) OVER STRANDS, INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/UB TOROUR
- BRING TERMINAL MAY BE CRIMPED ONTO WIRE 8 ATTACHED WITH TERMINAU SCREW AT 12 IN/LBS

SEE REVERSE SIDE FOR DEVICE DIMENSIONS

### CONNECTOR Model # 2P20GR



Cat # 20FR Female Panel Mount

- PANEL CUTOUT 780 X 2 020, 16 GAUGE, 060 MATERIAL
- PUSH DEVICE REARWARD THROUGH CUTOUT AND FIGHTEN MOUNTING SCREW TO 7 IN/LBS

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO CONDUCTIVE PANEL. MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL.

- WIRE TERMINATION TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS
- SLIP WIRE SMOE (PROVIDED) OVER STRANDS. INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/LB TORQUE
- #8 RING TERMINAL MAY BE CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 INC. 85

-SEE REVERSE SIDE FOR DEVICE DIMENSIONS

# ONNECTOR



LISTED 53Z2

Model # 2P20GR

### Cat # 20FR Female Panel Mount

PANEL CUTOUT, 760 X 2 020, 16 GAUGE, 060 MATERIAL

PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 INVEST TORQUE

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO <u>CONDUCTIVE PANEL</u>. MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL.

WIRE TERMINATION - TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS

- SLIP WIRE SHOE (PROVIDED) OVER STRANDS INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 INVLB TORQUE
- #8 RING TERMINAL MAY 86 CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 INVIRS ISEE REVERSE SIDE FOR DEVICE DIMENSIONS

CONNECTOR



LISTED  $53Z_{2}$ 

Model # 2P20GR

### Cat # 20FR Female Panel Mount

- PANEL CUTOUT 760 X 2 020, 16 GAUGE, 060 MATERIAL
- PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 INVESS TORQUE

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO CONDUCTIVE PANEL. MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL

- WIRE TERMINATION TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS
- SLIP WIRE SHOE (PROVIDED) OVER STRANDS, INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/LB TOROUS
- #8 RING TERMINAL MAY BE CRIMPED ONTO WIRE
   8 ATTACHED WITH TERMINAL SCREW AT 12 INc. BS

-SEE REVERSE SIDE FOR DEVICE DIMENSIONS.

CONNECTOR



LISTED 53Z2

Model # 2P20GR


### Cat # 20FR Female Panel Mount

- PANEL CUTOUT 760 X 2 020, 16 GAUGE, 060 MATERIAL
- PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 IN:LBS TORQUE

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO <u>CONDUCTIVE</u> <u>PANEL</u>. MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL.


- WIRE TERMINATION TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES. PANEL MOUNTS
- SUP WIRE SHOE (PROVIDED) OVER STRANDS, INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/LB TORQUE
- #8 RING TERMINA, MAY BE CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 INJUBS

-SEC REVERSE SIDE FOR DEVICE DIMENSIONS




Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

470106



Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com


470106



Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

470106


### DIMENSIONS IN INCHES.



Marinco 707 / 226-8600 FAX 707 / 259-2079 · www.marinco.com

470106


### DIMENSIONS IN INCHES



Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

470106


### DIMENSIONS IN INCHES.



Marineo 707 / 226-8600 FAX 707 / 259-2079 www.marineo.com

470106


### DIMENSIONS IN INCHES



Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

470106


### DIMENSIONS IN INCHES .



**Marinco** 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

707 / 259-2079 matrineo com 470106

### DIMENSIONS IN INCHES.



Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

470106