

CINTILLO 300MM X 3.6MM NEGRO PKT 100

REF. CHS-4X300B

- Material:** Aprobado por UL Nylon 66.
- Características:**
 - Bajo UL 94V-2.
 - Resistente a la erosión y envejecimiento.
 - Alta resistencia.
 - Inflamabilidad V2.
 - Cumple la UL (E359184).



REFERENCE	LENGTH (L)		WIDTH (W)	BUNNDLE DIAMETER (E)	TENSILE STRENGTH	
	INCH	MM	MM	MM	LBS	KGS
CHS-3X100B	4.0"	100	2.5	22	18	8
CHS-4X150B	6.0"	150	3.6	35	40	18
CHS-4X200B	8.0"	200	3.6	53	40	18
CHS-4X300B	11 5/8"	300	3.6	80	40	18
CHS-5X200B	8"	200	4.8	53	50	22
CHS-5X250B	10"	250	4.8	65	50	22
CHS-5X300B	11 5/8"	300	4.8	82	50	22
CHS-5X380B	15"	380	4.8	105	50	22
CHS-5X430B	17"	430	4.8	115	50	22
CHS-5X500B	19 11/16"	500	4.8	150	50	22
CHS-8X300B	11 5/8"	300	7.6	80	120	55
CHS-8X370B	14 1/4"	370	7.6	98	120	55
CHS-8X400B	15 3/4"	400	7.6	105	120	55



CE

TUV
PRODUCT SERVICE

CHS®

CHS-8X500B	19 11/16"	500	7.6	145	120	55
CHS-9X550B	21 1/16"	550	9.0	160	175	80
CHS-9X600B	23 5/8"	600	9.0	170	175	80
CHS-9X760B	30"	760	9.0	225	175	80
CHS-9X920B	36 1/4"	920	9.0	265	175	80
CHS-9X1020B	40 1/6"	1020	9.0	295	175	80