

2420





UPC Code: 07847780934

Country of Origin: Mexico - *Eligible for ARRA funded projects > \$7,443,000

NEMA: L15-20R





Locking Wiring Devices

Brand Features

Leviton's Industrial Grade Locking Devices are built to provide unparalleled quality and superior performance in the most severe industrial settings. Leviton combines the best materials available with superior production standards to produce a broad selection of Locking Devices of unmatched flexibility and dependability.

Item Description

20 Amp, 250 Volt 3-Phase, NEMA L15-20R, 3P, 4W, Flush Mtg Locking Receptacle, Industrial Grade, Grounding, V-0-MAX - BLACK

Technical Information

AC Horsepower Ratings
At Rated Voltage: 3 HP

Electrical Specifications
Grounding: Grounding
Amperage: 20 Amp
Voltage: 250 Volt 3-Phase

NEMA: L15-20R

Pole: 3 Wire: 4

Dielectric Voltage: Withstands 2000V per

UL498

Current Limiting: Full Rated Current Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications
Flammability: Rated V-0 per UL94
Operating Temperature: -40C to 60C

Material Specifications
Face Material: Ultramid
Base Material: Valox

Line Contacts: Brass .040 Thick Terminal Screws: Brass 10-32 Grounding Screw: Brass 8-32 Body Material: Nylon Cover Material: Valox 357 Line Contacts: Brass

Terminal Screws: Chromated Brass Grounding Screw: Chromated Brass Strap Material: Nickel-Plated Brass

Color: Black

Terminal Clamps: Nickel-Plated Brass

Ground Contacts: Brass

Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground,

White-Neutral

Terminal ID: Marked on Device
Terminal Accom.: 14-8 AWG
Product ID: Ratings and NEMA I.D.
permanently marked on device

Termination: Back & Side

Product Features

Face Material: Ultramid NEMA: L15-20R Base Material: Valox

Color: Black

Warranty: Lifetime Warranty

Standards and Certifications

NEMA: WD-6

NEMA: WD-1 & WD-6


ANSI: C-73 **UL:** 498

UL Fed Spec: W-C-596 **CSA:** C22.2 No. 42


NOM: 057

Warranty: Lifetime Limited

Dimensional Diagram



Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.
201 North Service Road, Melville, NY 11747
Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd.165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 · FAX: 1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2012-2015 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

*Buy American Compliant Logo -- The American Recovery And Reinvestment Act of 2009 ("ARRA") provides federal grants and loans for projects throughout the country. Section 1605 of the Act, named the "Buy American" provision, requires that certain materials and manufactured products used in projects funded by the Act be manufactured in the United States. The appearance of the Recovery Act Logo in relation to a Leviton product is only intended to reflect that such product may be used in an ARRA funded project. It does not mean that such product or Leviton is sponsored or endorsed by, or that Leviton receives funds from, the federal government or the Recovery Accountability and Transparency Board. Nothing in Leviton's use of the logo is intended to suggest anything regarding the requirements for funding under ARRA.

