



## CFJ225S

RCCB 2P 25A 300mA AC Class 60Hz

Technical attributes	CFJ225S
Altitude	2000 m
Bottom removability for modular devices	No
Construction size (DIN 43880)	1
Degree of pollution according to IEC 60664 / IEC 60947-2	2
Residual current trip mode	Undelayed
Short-time delayed tripping	No
Frequency	60 Hz
Height of installed product	83 mm
Idm: Breaking and opening capacity	1.5 kA
Idn	300 mA
Rated residual operating current	
IN	25 A
Rated current	
Inc	6 kA
Rated conditional short-circuit current Inc according to EN 61008-1	
IP	IP20
Protection index IP	
Largeur_produit_inst	35 mm
Width of installed product	
Fixing mode	Din-Rail
Number of modules	2
Number of poles	2
Electric endurance in number of cycles	2000

<b>Number of mechanical operations</b>	4000
<b>Withstand not tripping on 8-20 µs wave</b>	0.25 kA
<b>Neutral position</b>	left
<b>degree 360° product mounting position</b>	Yes
<b>Depth of installed product</b>	70 mm
<b>Connection cross-sect. rigid cable</b>	25mm <sup>2</sup>
<b>Connection cross-sect. flexible conductor</b>	16mm <sup>2</sup>
<b>Compatible with DIN rail mounting</b>	Yes
<b>Standard text</b>	IEC 61008-1
<b>Top removability for modular devices</b>	No
<b>Type of Bottom Connection for modular devices</b>	Biconnect
<b>Type of bottom rail clip for modular devices</b>	metallic
<b>Type of connection</b>	with screw
<b>Residual current type</b>	AC
<b>U<sub>e</sub></b>	127 V
<b>Rated operational voltage U<sub>e</sub></b>	
<b>U<sub>i</sub></b>	500 V
<b>Rated insulation voltage</b>	
<b>U<sub>imp</sub></b>	4000 V
<b>Rated impulse withstand voltage</b>	